

AX3000 Wi-Fi 6 PoE Router

X530P

Smart Wi-Fi, Easy Connections

- Wi-Fi 6 delivers faster speeds, greater capacity and reduced network congestion
- Wi-Fi 6 speeds up to 3 Gbps¹ to enjoy a smooth and uninterrupted online experience
- One 2.5 Gigabit PoE WAN port and two Gigabit Ethernet LAN ports provide high speed wired connectivity
- IEEE 802.3at compliant with PoE capability to connect D-Link 5G NR ODU
- Free D-Link Falcon app
- D-Link mesh compatible with G Series and X Series products



Ultra-Fast Speeds

Wi-Fi 6 technology to connect more devices with faster speeds



Safer Network

Parental control, guest Wi-Fi, WPA3[™] encryption and IEC 62443-4-1 certification



Gigabit Port

Connect to smart TV, game console, PC and more for fast and reliable connections




PoE Convenience

Powers PoE-enabled devices to save cost and reduce installation time




Easy Setup and Management

Set up your Wi-Fi in minutes with the D-Link Falcon app to effortlessly manage your network



Rear Panel



Technical Specifications

X530P

General

Device Interfaces	<ul style="list-style-type: none">• 1 x 2.5-Gigabit PoE WAN port• 2 x Gigabit Ethernet LAN ports• 1 x WPS button• 1 x Reset button• 1 x Power button• 1 x Power connector
Antenna Type	<ul style="list-style-type: none">• 2 x 2.4 GHz WLAN internal antennas• 2 x 5 GHz WLAN internal antennas
Wi-Fi Data Rates ¹	<ul style="list-style-type: none">• 5 GHz up to 2402 Mbps• 2.4 GHz up to 574 Mbps
IEEE Standard	<ul style="list-style-type: none">• IEEE 802.11ax/ac/n/g/b/a• IEEE 802.3u/ab

Functionality

Security Protocol	<ul style="list-style-type: none">• WPA (Wi-Fi Protected Access)• WPA2• WPA3
Firewall	<ul style="list-style-type: none">• Stateful Packet Inspection• Anti-spoofing Checking• IP/MAC Address Filtering• 1 x DMZ

Software

Device Management	<ul style="list-style-type: none">• D-Link Falcon app (iOS and Android)• Web UI
-------------------	--

Physical

LED	Power/Status/WPS
Dimensions	137 x 146 x 205 mm (5.39 x 5.74 x 8.07 in)
Weight	623 g (21.98 oz)
Power Adapter	12 V / 5 A
Operating Temperature	0 to 40 °C (32 to 104 °F)
Storage Temperature	-10 to 70 °C (14 to 158 °F)
Operating Humidity	10% to 90% non-condensing
Storage Humidity	0% to 95% non-condensing
Certifications	CE

Ordering Information

X530P	AX3000 Wi-Fi 6 PoE Router
-------	---------------------------

¹The maximum data rates mentioned are theoretical values. The actual data rates achieved may vary depending on the specific network environment and conditions.

²Supported frequency bands are dependent on regional variants and may not be available in all markets.