

Product Highlights

Feature-Rich Software

An integrated software image provides powerful L2 and L3 features to fulfill different applications' requirements, capable of building solid, reliable networks

Embedded 25G Ports

Four embedded high-speed 25G ports simplify the network deployment by providing versatile options for uplink connections

Scalability and High Availability

Physical stacking provides agile expansion and redundancy while reliability through fault tolerant topologies ensures rock-solid connectivity



DXS-3130-28

Layer 3 Stackable Managed Switch

Key Features

High Availability and Flexibility

- Variety of high-speed interface combinations to meet different network requirements
- 5-speed smart fan design automatically adjusts according to device operating temperature

Reliability

- Redundant power supply (RPS) support
- Ethernet Ring Protection Switching (ERPS)
- Embedded 6 kV surge protection on all Ethernet ports
- IEEE 802.1D/802.1w/802.1s Spanning Tree
- Loopback Detection (LBD)

L3 Features

- Static Route
- RIP/RIPng
- OSPFv2/v3

Operations, Administration and Maintenance

- IEEE 802.3ah Ethernet Link OAM
- IEEE 802.1ag/ITU-T Y.1731 Service OAM

High Bandwidth Stacking

- Physical stack of up to 9 units via four 25G ports
- 200 Gbps per device physical stacking bandwidth

The DXS-3130-28 Layer 3 Stackable Managed Switch is for secure connectivity in an enterprise or metro Ethernet access network and supports both multicasting and enhanced security, making it an ideal 10G/multi-Gigabit access layer solution. The DXS-3130-28 features 24 10G/multi-Gigabit ports and 4 10/25G SFP28 ports, offering a versatile and high-speed networking connection. The switch features 4 10/25G SFP28 ports for enhanced speed and versatility. It also includes a USB 2.0 port, enabling direct booting of images and uploading of configuration files, as well as convenient storage of syslog files on a USB 2.0 device.

Enhanced Network Reliability

The DXS-3130-28 targets enterprises and metro Ethernet applications, and customers who require a high level of network security and maximum uptime. The DXS-3130-28 features redundant power supply (RPS) and incorporate essential reliability features to enhance network resilience, including 802.1D Spanning Tree (STP), 802.1w Rapid Spanning Tree (RSTP), 802.1s Multiple Spanning Tree (MSTP), Loopback Detection (LBD), and Broadcast Storm Control. G.8032 Ethernet Ring Protection Switching (ERPS) minimizes recovery time to 50 ms. For load sharing and redundancy backup in a switch cascading/server attachment configuration, the DXS-3130-28 provides dynamic 802.3ad Link Aggregation Port Trunking.

Comprehensive Security

The DXS-3130-28 provides users with the latest security features such as Multi-layer and Packet Content Access Control Lists (ACL), Storm Control, and IP-MAC-Port Binding (IMPB) with DHCP Snooping. The IP-MAC-Port Binding feature allows administrators to bind a source IP address with an associated MAC and define the port number to enhance user access control. With the DHCP Snooping feature, the switch automatically learns IP/MAC pairs by snooping DHCP packets and saving them to the IMPB white list.

DXS-3130-28 Layer 3 Stackable Managed Switch

Intelligent Fan Operation

The DXS-3130-28 has built-in internal fans which can automatically start working to prevent the device from overheating. The fan speed will be gradually adjusted between 5 levels of cooling according to the operating temperature of the switch. Administrators can also configure the operation state of internal fans through Web UI or command line interface (CLI).

Easy Access Control Policies

The DXS-3130-28 supports authentication mechanisms such as 802.1X, Web-based Access Control (WAC), and MAC-based Access Control (MAC) for strict access control and easy deployment. After authentication, individual policies such as VLAN membership, QoS policies, and ACL rules can be assigned to each host.

Versatile Traffic Management

The DXS-3130-28 implements a rich set of multi-layer QoS/CoS features to ensure that critical network services such as VoIP, video conferences, IPTV, and IP surveillance are always given high priority. Traffic Shaping features guarantee bandwidth for these services when the network is busy. L2 Multicast support enables the DXS-3130-28 to handle growing IPTV applications.

Host-based IGMP/MLD Snooping feature allows for multiple multicast subscribers per physical interface while ISM VLAN allows the switches to send multicast streams in a multicast VLAN to save bandwidth and to provide better security to the backbone network. The ISM VLAN profiles allow administrators to bind or replace the pre-defined multicast registration information to subscriber ports quickly and easily.

High Availability and Flexibility

The DXS-3130-28 allows multiple switches to be combined to form a single physical or virtual stack. This increases redundancy over multiple physical units, simplifies management, and provides a single IP address to manage all members in the stack. Up to 9 switches can be combined using DACs/Fibers to make up to 200 Gigabit Ethernet ports available, allowing switching capacity to be increased with demand.

6 kV Surge Protection

The DXS-3130-28 features built-in 6 kV surge protection on all Ethernet access ports, and requires no external surge protection equipment. This effectively protects the switches against sudden electrical surges caused events such as lightning strikes or unstable electrical current. Built-in 6 kV surge protection significantly reduces the chances of equipment being damaged from electrical surges, and effectively lowers maintenance costs by minimizing the need for expensive equipment repairs or replacement.

Manageability

D-Link's Single IP Management (SIM) feature simplifies and speeds up management tasks, allowing multiple switches to be configured, monitored, and maintained from any workstation running a web browser and with network connectivity. All switches can be managed as a virtual stack, allowing physically separate switches to be managed using a single IP address. The DXS-3130-28 also supports management tools such as a Web UI, SSH, Telnet, and console, and standards-based protocols such as SNMP, RMON, and SSL.

DXS-3130-28 Layer 3 Stackable Managed Switch

Technical Specifications

| Interface | | |
|---------------------------------|---|--------------------------------|
| Ports | • 24 x 100M/1G/2.5G/5G/10GBASE-T ports | • 4 x 10/25G SFP28 ports |
| Optional Redundant Power Supply | • DPS-500A | • DPS-500DC |
| Console Port | 10/100/1000BASE-T RJ-45 port for out-of-band CLI management | |
| Management Port | 10/100/1000BASE-T RJ-45 port for out-of-band IP management | |
| Stacking Ports | 4 | |
| Stacking Ports | 1 x USB 2.0 Type A port | |
| Performance | | |
| Switching Capacity | 680 Gbps | |
| 64-Byte Packet Forwarding Rate | 505.92 Mpps | |
| Packet Buffer Memory | 4 MB | |
| Physical | | |
| MTBF (Hours) | 317,350.54 hours | |
| Acoustics | • Max: 53.9 dB (fan high speed) | • Min: 30.6 dB (fan low speed) |
| Heat Dissipation | 261.291 BTU/h | |
| Power Input | 100 to 240 VAC, 50 to 60 Hz | |
| Maximum Power Consumption | • Maximum: 76.58 W | • Standby: 32.857 W |
| Dimensions (W x D x H) | 440 x 250 x 44 mm (17.32 x 9.84 x 1.73 in) | |
| Weight | 3.525 kg | |
| Ventilation | 3 x smart fans | |
| Power Surge Protection | IEC61000-4-5 6kV surge protection on all Ethernet ports | |
| Operating Temperature | 0 to 50°C (32 to 122°F) | |
| Storage Temperature | -40 to 70°C (-40 to 158°C) | |
| Operating Humidity | 10% to 90% relative humidity | |
| Storage Humidity | 5% to 90% relative humidity | |
| Emission (EMI) | • FCC Class A • CE Class A • VCCI Class A | • IC • RCM • BSMI |
| Safety | • CB • cUL | • BSMI |

DXS-3130-28 Layer 3 Stackable Managed Switch

Software Features

| | | |
|--------------------|--|--|
| Stackability | <ul style="list-style-type: none"> Physical stacking <ul style="list-style-type: none"> Up to 9 units per stack Up to 200 Gbps stacking bandwidth Ring/chain topology support | <ul style="list-style-type: none"> Virtual stacking <ul style="list-style-type: none"> D-Link Single IP Management (SIM) Up to 32 units per virtual stack |
| L2 Features | <ul style="list-style-type: none"> MAC Address Table: 32K (32,768) entries <ul style="list-style-type: none"> Flow Control 802.3x Flow Control HOL Blocking Prevention Jumbo Frames up to 12 Kbytes 802.1AX/802.3ad Link Aggregation <ul style="list-style-type: none"> Max. 32 groups per device, 8 ports per group Spanning Tree Protocols <ul style="list-style-type: none"> 802.1D STP 802.1w RSTP 802.1s MSTP BPDU Filtering Root Guard Loop Guard | <ul style="list-style-type: none"> Loopback Detection Port Mirroring <ul style="list-style-type: none"> One-to-One, Many-to-One Mirroring for both Tx/Rx 4 mirroring groups Flow mirroring <ul style="list-style-type: none"> Supports Mirroring for Tx/Rx VLAN Mirroring RSPAN L2 Protocol Tunneling Ethernet Ring Protection Switching (ERPS) v1/v2 |
| L2 Multicasting | <ul style="list-style-type: none"> IGMP Snooping <ul style="list-style-type: none"> IGMP v1/v2/v3 Snooping 1024 IGMP groups IGMP Snooping Fast Leave 128 static IGMP groups Per VLAN IGMP Snooping Data Driven Learning IGMP Snooping Querier IGMP Authentication IGMP Accounting | <ul style="list-style-type: none"> Report Suppression MLD Snooping <ul style="list-style-type: none"> MLD v1/v2 Snooping 1024 MLD Groups MLD Snooping Fast Leave 64 static MLD groups MLD Snooping Querier Per VLAN MLD Snooping MLD Proxy Reporting |
| L3 Multicasting | <ul style="list-style-type: none"> IGMP v1/v2/v3 | <ul style="list-style-type: none"> PIM-SM for IPv4 |
| VLAN | <ul style="list-style-type: none"> VLAN Group <ul style="list-style-type: none"> Max. 4K VLAN groups Max. 1~4094 VIDs GVRP <ul style="list-style-type: none"> Max. 4K dynamic VLAN groups Double VLAN (Q-in-Q) <ul style="list-style-type: none"> Port-based Q-in-Q Selective Q-in-Q 802.1Q Auto Surveillance VLAN Port-based VLAN | <ul style="list-style-type: none"> 802.1v Protocol-based VLAN Voice VLAN MAC-based VLAN VLAN translation Multicast VLAN (ISM VLAN for IPv4/IPv6) Asymmetric VLAN Private VLAN VLAN Trunking Super VLAN |
| Quality of Service | <ul style="list-style-type: none"> 802.1p 8 queues per port Queue Handling <ul style="list-style-type: none"> Strict Priority Weighted Round Robin (WRR) Strict + WRR Weighted Deficit Round Robin (WDRR) Policy Map <ul style="list-style-type: none"> Remark 802.1p priority Remark IP precedence/DSCP Congestion Control <ul style="list-style-type: none"> Weighted Random Early Detection (WRED) CoS based on <ul style="list-style-type: none"> Switch port Inner/Outer VID Inner/Outer 802.1p Priority MAC address IP address DSCP Protocol type TCP/UDP port IPv6 traffic class IPv6 flow label | <ul style="list-style-type: none"> Bandwidth Control <ul style="list-style-type: none"> Port-based (ingress/egress, min. granularity 8 Kbps) Flow-based (ingress/egress, min. granularity 8 Kbps) Per queue bandwidth control (min. granularity 8 Kbps) Three Color Marker <ul style="list-style-type: none"> CIR/PIR minimum granularity: 8 kbps trTCM srTCM |

DXS-3130-28 Layer 3 Stackable Managed Switch

| | | |
|--|---|---|
| Access Control List (ACL) | <ul style="list-style-type: none"> • ACL based on <ul style="list-style-type: none"> • 802.1p priority • VID • MAC address • Ether Type • LLC • VLAN • IP address • IP preference/ToS • DSCP mask • Protocol type • TCP/UDP port number • IPv6 Traffic Class • IPv6 Flow Label | <ul style="list-style-type: none"> • Time-based ACL • CPU Interface Filtering • Max. ACL entries: <ul style="list-style-type: none"> • Ingress (hardware entries): 3072 • Egress (hardware entries): 1024 • VLAN Access Map Numbers: 100 |
| Security | <ul style="list-style-type: none"> • Port Security <ul style="list-style-type: none"> • Supports up to 64 MAC addresses per port • Broadcast/Multicast/Unicast Storm Control • D-Link Safeguard Engine • DHCP Server Screening • IP Source Guard • DHCP Snooping • IPv6 Snooping • Dynamic ARP Inspection (DAI) • DHCPv6 Guard • IPv6 Route Advertisement (RA) Guard • IPv6 ND Inspection • Duplicate Address Detection (DAD) • ARP Spoofing Prevention <ul style="list-style-type: none"> • Max. 64 entries | <ul style="list-style-type: none"> • L3 Control Packet Filtering • Traffic Segmentation • SSL <ul style="list-style-type: none"> • TLS 1.0/1.1/1.2 • IPv4/IPv6 access • SSH <ul style="list-style-type: none"> • Supports SSH v2 • Supports IPv4/IPv6 access • BPDU Attack Protection • DoS Attack Prevention |
| AAA | <ul style="list-style-type: none"> • Guest VLAN • 802.1X Authentication <ul style="list-style-type: none"> • Supports port/host-based access control • Identity-driven Policy Assignment • Dynamic VLAN Assignment • Ingress/Egress Bandwidth Control • ACL Assignment • Privilege Level for Management Access • Trusted Host • RADIUS/TACACS+ Accounting • Web-based Access Control (WAC) <ul style="list-style-type: none"> • Port/host-based access control • Identity-driven Policy Assignment • Dynamic VLAN Assignment • Support IPv4 access • Ingress/Egress Bandwidth Control • ACL Assignment | <ul style="list-style-type: none"> • RADIUS and TACACS+ Authentication • Authentication Database Failover • Compound Authentication • MAC-based Access Control (MAC) <ul style="list-style-type: none"> • Supports port/host-based access control • Identity-driven Policy Assignment • Dynamic VLAN Assignment • Ingress/Egress Bandwidth Control • ACL Assignment |
| Green Features | <ul style="list-style-type: none"> • Energy-Efficient Ethernet (EEE) • Power saving by link status • Power saving by LED shut-off | <ul style="list-style-type: none"> • Power saving by port shut-off • Power saving by system hibernation |
| OAM (Operations, Administration and Maintenance) | <ul style="list-style-type: none"> • 802.3ah Ethernet Link OAM • D-Link Unidirectional Link Detection (DULD) • Dying Gasp | <ul style="list-style-type: none"> • 802.1ag Connectivity Fault Management (CFM) • Y.1731 OAM • Optical Transceiver Digital Diagnostic Monitoring (DDM) |
| L3 Features | <ul style="list-style-type: none"> • IPv4 ARP Entries 4096 <ul style="list-style-type: none"> • 256 Static ARP • IPv6 ND Entries:1024 <ul style="list-style-type: none"> • 128 Static ND Entries • IP Interface <ul style="list-style-type: none"> • 128 interfaces | <ul style="list-style-type: none"> • Gratuitous ARP • Loopback Interface • Proxy ARP <ul style="list-style-type: none"> • Local ARP proxy • VRRP v2/v3 • IP Helper |

DXS-3130-28 Layer 3 Stackable Managed Switch

| | | |
|-------------------------|--|--|
| L3 Routing | <ul style="list-style-type: none"> • 1024 hardware routing entries shared by IPv4/IPv6 <ul style="list-style-type: none"> • 1 entry consumed by each IPv4 route • 2 entries consumed by each IPv6 route • Up to 16K IPv4 / 8K IPv6 hardware L3 forwarding entries <ul style="list-style-type: none"> • 1 entry consumed by each IPv4 route • 2 entries consumed by each IPv6 route • IPv4/IPv6 Static Route <ul style="list-style-type: none"> • Max. 512 IPv4 entries • Max. 256 IPv6 entries • Equal-Cost Multi-Path Route (ECMP) • IPv4/IPv6 Default Route | <ul style="list-style-type: none"> • PBR (Policy-based Route) • Null Route • Route Preference • Route Redistribution • RIPv1/v2/ng • OSPF <ul style="list-style-type: none"> • OSPF v2/v3 • OSPF passive interface • Stub/NSSA area • Equal-Cost Multi-Path Route (ECMP) • Text/MD5 |
| Management | <ul style="list-style-type: none"> • Web-based GUI <ul style="list-style-type: none"> • Support IPv4/IPv6 access • Support SSL (HTTPS) • Command Line Interface (CLI) • Telnet Server for IPv4/IPv6 • Telnet Client for IPv4/IPv6 • TFTP Client for IPv4/IPv6 • DNS Client for IPv4/IPv6 • Secure FTP Server for IPv4/IPv6 • SNMP <ul style="list-style-type: none"> • v1/v2c/v3 • IPv4/IPv6 access • SNMP Traps • System Log for IPv4/IPv6 Syslog Server • sFlow • Multiple images/ Multiple Configurations • RMON v1: <ul style="list-style-type: none"> • 1, 2, 3, 9 groups • RMON v2: <ul style="list-style-type: none"> • ProbeConfig group • LLDP/LLDP-MED • BootP/DHCP Client | <ul style="list-style-type: none"> • DHCP Auto-Configuration • DHCP/DHCPv6 Local Relay • DHCP Relay Option 60/61/82/125 • Flash File System • PPPoE Circuit-ID Tag Insertion • D-Link Discover Protocol (DDP) • Debug command • Support IPv4/v6 SNTP Server • NTPv3/v4 • Password recovery/ encryption • DHCP server <ul style="list-style-type: none"> • Support for IPv4/IPv6 address assignment • Command Logging • SMTP • DHCPv6 Prefix Delegation (PD) • Ping/ Traceroute for IPv4/IPv6 • Microsoft® Network Load Balancing (NLB) |
| MIB | <ul style="list-style-type: none"> • RFC1065, RFC1066, RFC1155, RFC1156, RFC2578 MIB Structure • RFC1212 Concise MIB Definitions • RFC1213 MIBII • RFC1215 MIB Traps Convention • RFC1493, RFC4188 Bridge MIB • RFC1157, RFC2571, RFC2572, RFC2573, RFC2574, RFC2575, C2576 SNMP MIB • RFC1442, RFC1901, RFC1902, RFC1903, RFC1904, RFC1905, RFC1906, RFC1907, RFC1908, RFC2578, RFC3418, RFC3636 SNMPv2 MIB • RFC271, RFC1757, RFC2819 RMON MIB • RFC2021 RMONv2 MIB • RFC1398, RFC1643, RFC1650, RFC2358, RFC2665, RFC3635 Etherlike MIB • RFC2668 802.3 MAU MIB • RFC2674, RFC4363 802.1p MIB • Interface Group MIB • RFC2618 RADIUS Authentication Client MIB • RFC4022 MIB for TCP • RFC4113 MIB for UDP | <ul style="list-style-type: none"> • RFC2620 RADIUS Accounting Client MIB • RFC2925 Ping & TRACEROUTE MIB • TFTP uploads and downloads (D-Link MIB) • Trap MIB (D-Link MIB) • Entity MIB • VRRP MIB • RIPv2 MIB • RFC1850, RFC5643 OSPF MIB • RFC4293 IPv6 SNMP Mgmt Interface MIB • DDM MIB (D-Link MIB) • Private MIB • MIB for D-Link Zone Defense • RFC3621 Power Ethernet MIB • DDP MIB • LLDP-MED MIB • IP Forwarding Table MIB |
| RFC Standard Compliance | <ul style="list-style-type: none"> • RFC 768 UDP • RFC 791 IP • RFC 793 TCP • RFC 826 ARP • RFC 3513, 4291, IPv6 Addressing Architecture • RFC2474, RFC3168, RFC3260 Definition of the DS Field in the IPv4 and IPv6 Headers • RFC1321, RFC2284, RFC2865, RFC2716, RFC1759, RFC3580, RFC3748 Extensible Authentication Protocol (EAP) • RFC2571 SNMP Framework • RFC 2068, 2616 HTTP • RFC 2866 RADIUS Accounting • RFC792 ICMPv4 • RFC2463, RFC4443 ICMPv6 | <ul style="list-style-type: none"> • RFC4884 Extended ICMP to support Multi-Part Messages • RFC1338, RFC1519 CIDR • RFC2574 User-based Security Model for SNMPv3 • RFC1981 Path MTU Discovery for IPv6 • RFC2460 IPv6 • RFC 2571, 2572, 2573, 2574, SNMP • RFC 854 Telnet • RFC 951, 1542 BootP • RFC2461, RFC4861 Neighbor Discovery for IPv6 • RFC2462, RFC4862 IPv6 Stateless Address Autoconfiguration (SLAAC) • RFC2464 IPv6 over Ethernet and definition • RFC1886 DNS extension support for IPv6 |

DXS-3130-28 Layer 3 Stackable Managed Switch

Order Information

| | |
|-------------|---|
| DXS-3130-28 | 24 Ports 10G + 4 Ports 25G SFP28 Managed Switch |
|-------------|---|

Optional Direct Attach Cables

| | |
|-------------------|---|
| DEM-CB100S | 1 m 10G SFP+ Direct Attach Cable (DAC) |
| DEM-CB300S | 3 m 10G SFP+ Direct Attach Cable (DAC) |
| DEM-CB700S | 7 m 10G SFP+ Direct Attach Cable (DAC) |
| DEM-CB100Q28-4S28 | 1 m 100G QSFP28 to 4x 25G SFP28 Direct Attach Cable (DAC) |
| DEM-CB100S28 | 1 m 25G SFP28 Direct Attach Cable (DAC) |

Optional Redundant Power Supplies

| | |
|-----------|---------------------------|
| DPS-500A | AC Redundant Power Supply |
| DPS-500DC | DC Redundant Power Supply |

Optional SFP+ Transceivers

| | |
|---------------|--|
| DEM-410T | 10GBASE-T Copper SFP+ Transceiver (w/o DDM), 30 m |
| DEM-431XT | 10GBASE-SR Multi-Mode, OM1:33M/OM2:82M/OM3:300M (w/o DDM) |
| DEM-432XT | 10GBASE-LR Single-Mode, 10 km (w/o DDM) |
| DEM-433XT | 10GBASE-ER Single-Mode, 40 km (w/o DDM) |
| DEM-434XT | 10GBASE-ZR Single-Mode, 80 km (w/o DDM) |
| DEM-435XT | 10GBASE-LRM Multi-Mode, 200M (w/o DDM) |
| DEM-436XT-BXD | 10GBASE-LR Single-Mode, 20 km (TX-1330/RX-1270 nm) (w/o DDM) |
| DEM-436XT-BXU | 10GBASE-LR Single-Mode, 20 km (TX-1270/RX-1310 nm) (w/o DDM) |

Optional 25 Gigabit Ethernet SFP28 Transceivers

| | |
|-------------|---|
| DEM-S2801SR | 25G SFP28 Multi-Mode, 100 m Transceiver |
| DEM-S2810LR | 25G SFP28 Single-Mode 10 km Transceiver |